

FLUSHING FLUID

Our Thermal Fluid Solutions Flushing Fluid is a pioneering flushing fluid compatible and miscible with synthetic and heat transfer fluid, it quickly and effectively removes deposits left on interior surfaces by oxidized, thermally degraded fluid.

PERFORMANCE BENEFITS

- **Fast and Easy** – quicker than chemical cleaning and requiring less system downtime; simply drain the old fluid, add Flushing Fluid and circulate before draining and re-filling with your new heat transfer fluid.
- **Safety** – this Flushing Fluid is a synthetic hydrocarbon with a high flash point and high initial boiling point, making it significantly safer to use than other cleaning solvents.
- **Environmentally Friendly** – outstanding regulatory status for minimum environmental reporting requirements.
- **Cost Effective** – compared to chemical cleaning for severely degraded or contaminated heat transfer systems.



20 Hallsteads, Doveholes, Derbyshire, SK17 8BJ. UK
+ 44 (0) 1298 815862 (UK) + 1 864-516-7506 (USA)

www.thermalfluidsolutions.com

FLUSHING FLUID PRODUCT SPECIFICATION

Appearance	Amber liquid
Composition	Synthetic hydrocarbon
Flash point, COC (ASTM D-92)	120°C (250°F)
Liquid density at 25°C (ASTM D-4052)	0.96 - 1.00 g/cm ³
Moisture content, maximum (ASTM E-203)	500 ppm

Contact the **TFS Team** today on **+44 (0)1298 815862**
or visit www.thermalfluidsolutions.com