



**THERMAL
FLUID
SOLUTIONS**

www.thermalfluidsolutions.com

UK Head Office: 20 Hallsteads,
Doveholes, Derbyshire, SK17 8BJ
+44 (0) 1298 815862

US Office: 42 S Bethany Bend Cir,
The Woodlands, Texas, TX 77382
+1 346-226-4092

PRODUCT
INFORMATION

FLUSHING FLUID

Our Thermal Fluid Solutions Flushing Fluid is a pioneering flushing fluid compatible and miscible with synthetic and heat transfer fluid, it quickly and effectively removes deposits left on interior surfaces by oxidized, thermally degraded fluid.

PERFORMANCE BENEFITS

- **Fast and Easy** – quicker than chemical cleaning and requiring less system downtime; simply drain the old fluid, add Flushing Fluid and circulate before draining and re-filling with your new heat transfer fluid.
- **Safety** – this Flushing Fluid is a synthetic hydrocarbon with a high flash point and high initial boiling point, making it significantly safer to use than other cleaning solvents.
- **Environmentally Friendly** – outstanding regulatory status for minimum environmental reporting requirements.
- **Cost Effective** – compared to chemical cleaning for severely degraded or contaminated heat transfer systems.



THERMAL FLUID SOLUTIONS

www.thermalfluidsolutions.com

UK Head Office: 20 Hallsteads,
Doveholes, Derbyshire, SK17 8BJ
+44 (0) 1298 815862

US Office: 42 S Bethany Bend Cir,
The Woodlands, Texas, TX 77382
+1 346-226-4092

FLUSHING FLUID PRODUCT SPECIFICATION

| | |
|--|-------------------------------|
| Appearance | Amber liquid |
| Composition | Synthetic hydrocarbon |
| Flash point, COC (ASTM D-92) | 120°C (250°F) |
| Liquid density at 25°C (ASTM D-4052) | 0.96 - 1.00 g/cm ³ |
| Moisture content, maximum (ASTM E-203) | 500 ppm |

Email the **TFS Team**, office@thermalfluidsolutions.com
or visit www.thermalfluidsolutions.com